

TECHNICAL DATA SHEET

XA5 LP

Cut-resistant gloves

Article NO: A5111

Material: gray seamless knit counter-cutting
Palm: leather reinforced palm

Size: 7"/ S - 11"/2 XL



Gloves are meant for protection against mechanical and thermal risks.

LEVELS OF PROTECTION:

EN 388



MECHANICAL RISKS

abrasion resistance:	4
cut resistance:	5
tear resistance:	4
puncture resistance:	4
cut resistance (TDM):	D

EN 407



THERMAL RISKS

fire resistance:	X
contact heat resistance:	1
convection heat resistance:	X
heat of radiation resistance:	X
small spatter resistance:	X
big spatter resistance:	X

This personal protective equipment is in conformity with these harmonized European Standards:

ČSN EN 420:2003+A1 2009 : Protective gloves - General requirements and test methods.

ČSN EN 388:2016 : Protective gloves against mechanical risks. (4-5-4-4-D)

ČSN EN 407:2004 : Protective gloves against thermal risks. (X-1-X-X-X)

Certified by notified body č. 2369 (VIPO a.s., Partizánske, Slovakia),

Certificate no 00156/111/1/2018.

Pairs in carton:	120
Carton weight:	23 kg
Carton size:	0,061 m ³
Polybag packing (pairs):	12

Store in dry and dark environment. Clean dirt with brush. Gloves can not be washed or cleaned chemically. Do not expose gloves to heat of radiation, organic solvents and their fumes, lubricants, grease, mineral oils, caustics and water.

Warning: Gloves can not be used in environment where there is risk of glove being caught by moving parts of machine.