



TECHNICAL SHEET

FA 30 304 18

Designation :

Energy absorbing webbing lanyard

- Energy absorbing webbing lanyard in 35 mm wide webbing which reduces the impact of the fall to less than 6 kN
- 30 mm wide polyester webbing lanyard
- Loops protected by an abrasion resistant tubular webbing.

Connectors :

1 scaffold hook, opening 55 mm, ref. FA5020755 and 1 screw-locking karabiner, opening 17 mm ref. FA5010117

Compliance :

EN355 : 2002 and tested as per VG11 of PPE Directive 89/686/EEC



Length :

Lg : 1.8 mtr (connectors included)

Materials :

Lanyard : polyester

Absorber : polyester and polyamide

Connectors : steel

HS code

56090090

Carton size / Pieces

66x38x24 / 25

Unit Weight

1.05 kg

AET : N°4303 Issue 4 Extension 1

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11 : GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



maj : 09/12

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

