



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

# ARDON® CREATRON® LOW S3 ESD

SAFETY SHOES



**DRY AIR**



**REFLECTIVE**



**WATER  
REPELLENT**



**NONMETALLIC**



**ESD**

TECHNICAL SHEET



**ARDON**<sup>®</sup>  
**WORKWEAR**  
**& OUTDOOR**

# ARDON<sup>®</sup> CREATRON<sup>®</sup> LOW S3 ESD

SAFETY SHOES

**ARTICLE** G3413

**MATERIAL**

Upper PES fabric, hydrofobic  
 Lining MESH laminated breathable fabric  
 Sole phylon/rubber, cemented technology  
 Toe cap glassfiber  
 Plate kevlar  
 Insole Anatomic HI POLY FOAM

**SIZE** 36-48

**UNIT** pair

**PACKAGE**

Units in a carton 10 pairs  
 Units in a box 1 pair

**DIMENSIONS**

|                       | 36-39        | 40-42            | 43-48         |
|-----------------------|--------------|------------------|---------------|
| Carton H x W x D (cm) | 61 x 32 x 38 | 63,5 x 34 x 40,5 | 64x 36,5 x 42 |
| Carton (cbm)          | 0,0742       | 0,0874           | 0,0981        |



TECHNICAL SHEET

| Size EUR         | 35 | 36   | 37   | 38   | 39   | 40   | 41   | 42   | 43   | 44   | 45   | 46   | 47   | 48   | 49 | 50 | 51 |
|------------------|----|------|------|------|------|------|------|------|------|------|------|------|------|------|----|----|----|
| Insole length mm | -  | 241  | 248  | 254  | 260  | 267  | 273  | 280  | 286  | 292  | 299  | 305  | 311  | 318  | -  | -  | -  |
| Foot length      | -  | 23,6 | 24,3 | 24,9 | 25,5 | 26,2 | 26,8 | 27,5 | 28,1 | 28,7 | 29,4 | 30,0 | 30,6 | 31,3 | -  | -  | -  |

**DESCRIPTION**

Safety half-boot with a quick-closing lacing system of a proven brand FITGO. A very stable and comfortable sole ensures safety in various types outdoor terrain. The upper of the shoe has an above-standard mechanical resistance stress.



**ARDON**<sup>®</sup>  
**WORKWEAR**  
 & **OUTDOOR**

## NORMS

(EU) 2016/425

EN ISO 20345:2022 Personal protective equipment – Safety footwear

EN IEC 61340-4-3:2018 Electrostatics: Standard test methods for specific application – Footwear

Category S3S SR FO

| Categories                                                                                     | EN ISO 20345 |  |
|------------------------------------------------------------------------------------------------|--------------|--|
| E - energy absorption in the heel area                                                         | ✓            |  |
| FO - resistance to oils and fuels                                                              | ✓            |  |
| A - antistatic footwear                                                                        | ✓            |  |
| SR3 - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin | ✓            |  |
| WR - upper resistant to water                                                                  | ✓            |  |
| Safety toe cap for toe protection                                                              | ✓            |  |
| P - resistance to punctures (protective insole)                                                | ✓            |  |
| HRO - resistance to contact heat up to 300 °C                                                  |              |  |
| HI-insulation of the bottom of the shoe against heat                                           |              |  |
| CI-insulation of the bottom of the shoe against the cold                                       |              |  |
| Splatters of molten metal                                                                      |              |  |
| ESD – shoe protects against electrostatic discharge and can be used on EPA premises            | ✓            |  |
| The shoes do not contain metal parts                                                           | ✓            |  |
| -                                                                                              |              |  |
| -                                                                                              |              |  |
| -                                                                                              |              |  |

TECHNICAL SHEET



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

| <b>CODE</b> | <b>EAN</b>    | <b>CARTON WEIGHT<br/>(KG)</b> | <b>UNIT WEIGHT<br/>(KG)</b> |
|-------------|---------------|-------------------------------|-----------------------------|
| G3413/36    | 8592390354402 | 11.0                          | 1.10                        |
| G3413/37    | 8592390354419 | 11.6                          | 1.16                        |
| G3413/38    | 8592390354426 | 12.1                          | 1.21                        |
| G3413/39    | 8592390354433 | 12.5                          | 1.25                        |
| G3413/40    | 8592390354440 | 12.8                          | 1.28                        |
| G3413/41    | 8592390354457 | 13.0                          | 1.30                        |
| G3413/42    | 8592390354464 | 13.5                          | 1.35                        |
| G3413/43    | 8592390354471 | 14.0                          | 1.40                        |
| G3413/44    | 8592390354488 | 14.8                          | 1.48                        |
| G3413/45    | 8592390354495 | 15.0                          | 1.50                        |
| G3413/46    | 8592390354501 | 15.5                          | 1.55                        |
| G3413/47    | 8592390354518 | 16.0                          | 1.60                        |
| G3413/48    | 8592390354525 | 16.6                          | 1.66                        |





**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**





**ARDON®**

**WORKWEAR  
& OUTDOOR**



TECHNICAL SHEET