

## TECHNICAL DATA SHEET

### LITE TOUCH OIL

Dipped gloves

Article NO: A8015

Material: extra fine nylon liner,  
coated in nitrile

Size: 6"/ XS - 11"/ 2XL



Gloves are meant for protection against mechanical risks.

#### LEVELS OF PROTECTION:



#### MECHANICAL RISKS

abrasion resistance:	2
cut resistance:	1
tear resistance:	2
puncture resistance:	1
cut resistance (TDM):	X

This personal protective equipment is in conformity with these harmonized European Standards:

EN ISO 21420:2020 : Protective gloves- general requirements and test methods  
EN 388:2016+A1:2018 : Protective gloves against mechanical risks (2-1-2-1-X)

Certified by notified body no. 0075 (CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France), dated 24<sup>th</sup> August 2020, certificate number 0075/2737/162/08/20/2225.

Pairs in carton: 144  
Carton weight: 4,6 kg  
Carton size: 0,054 m<sup>3</sup>  
Polybag packing (pairs): 12

Store in dry and dark environment. Clean dirt with brush. Gloves can not be washed or cleaned chemically. Do not expose gloves to heat of radiation, organic solvents and their fumes, lubricants, grease, mineral oils, caustics and water.

Warning: Gloves can not be used in environment where there is risk of glove being caught by moving parts of machine.