



# TECHNICAL DATA SHEET

---

## INTERFACE PLUS 38.33

**Artikl:** A5500

**Description :** Flock lined nitrile gloves, 15mil

**Features &** \* Nitrile rubber for solvent resistance

**Benefits :** \* Outstanding abrasion resistance

\* Anti-slip pattern for good grip in wet and dry conditions

\* Straight cuff

\* Ingredients comply with FDA regulations for food contact

\* Manufactured under a stringent quality management system

**Applications :** Industrial Cleaning,Petrochemical Industry,Aerospace and Automobile Industry,Printing Industry,Surface Coating,Metal Fabrication

**Product Details :**

Elastomer : Nitrile rubber

Thickness : 0.38 mm +/- 0.05

Lining : Flocklined

Former : Reverse Lozenge, CVIL

Cuff type : Straight

Exterior : Matt finish

Colours : Green G8, Blue B14

**CE Certification :** Conforms to European Council Directive 89/686/EEC relating to (Complex Design) Personal Protective Equipment after assessment against standards EN 374, EN 388 & EN 420:2003



**Chemical Risks**  
EN 374



**Mechanical Risks**  
EN 388



**Micro O. Risks**  
EN 374

Chemical Risks	Mechanical Risks	Micro O. Risks
Methanol	Level 3 Abrasion resistance	Level 4 Air leak test Passed
n-Heptane	Level 6 Blade cut resistance	Level 1 Water leak test Passed
Sodium hydroxide, 40%	Level 6 Tear resistance	Level 0
Sulphuric acid, 95-98%	Level 4 Puncture resistance	Level 1
Acetic acid, glacial	Level 3	
Acetonitrile	Level 1	
Ammonium hydroxide (33% NH <sub>3</sub> )	Level 5	
Amyl acetate	Level 3	
Amyl alcohol	Level 6	
Butanol	Level 6	
Butyl acetate	Level 2	
Butyl cellosolve (CAS 111-76-2)	Level 6	
Carbon disulphide	Level 1	
Chlorine gas	Level 6	
Cyclohexane	Level 6	
Cyclohexanol	Level 6	
Di-isobutyl ketone	Level 5	
Diethylene glycol	Level 6	
Dimethyl acetamide (CAS 127-19-5)	Level 1	
Dimethyl sulphoxide	Level 2	
Ethanol, 95%	Level 5	
2-Ethoxy ethanol	Level 4	
2-Ethoxy ethyl acetate	Level 3	
Ethyl acetate	Level 1	
Ethylene glycol	Level 6	
Ethyl ether	Level 2	
Formaldehyde, 37%	Level 6	
Hexane	Level 6	
Hydrazene monohydrate (64-65% H <sub>2</sub> H <sub>4</sub> ) (CAS 7803-57-8)	Level 6	
Hydrochloric acid, 37%	Level 6	
Hydrofluoric acid, 40%	Level 4	
Hydrogen peroxide 30% (CAS 7722-84-1)	Level 6	
Isopropanol	Level 6	
Iso octane	Level 6	
Kerosene	Level 6	
Lactic acid, 85%	Level 6	
Maleic acid (saturated)	Level 6	
Methyl methacrylate	Level 1	
Methyl propyl ketone	Level 1	
Methyl tert-butyl ether	Level 5	
Naptha solvent	Level 5	
Nitric acid, 40%	Level 6	
Octyl alcohol	Level 6	
Orthophosphoric acid, 85%	Level 6	
Perchloric acid	Level 6	
Petroleum ether (CAS 8032-32-4)	Level 6	
Petrol unleaded	Level 6	
Potassium hydroxide, 50%	Level 6	
Propyl acetate	Level 1	
Sodium hydroxide, 50%	Level 6	
Sodium hypochlorite, 10-15%	Level 6	



1,1,2,2-tetrachloroethane	Level 1
Tetrachloroethylene	Level 5
1,1,1-trichloroethane	Level 1
Toluene	Level 1
Turpentine	Level 6
White spirit (CAS 8052-41-3)	Level 6
White spirit (CAS 64742-48-9)	Level 6
White spirit (CAS 68551-17-7)	Level 6
Xylene (mixture of isomers)	Level 2

Conforms to : ASTM D4679 of 2002

Physical Dimensions :	Size	Palm	Wrist	Cuff	Length
	6 1/2	199	212	274	380
	7 1/2	213	226	282	380
	8 1/2	227	241	286	380
	9	228	245	293	380
	10	247	261	308	380

Circumference in mm,+/- 5 mm      Tolerance +/- 10 mm