

# TECHNICAL DATA SHEET

## MEL

Welding and heat resistant gloves

Article NO: A2007

Material: cowsplit leather  
Lining: without  
Cuff: 15 cm

Size: 10"/ XL



Gloves are meant for protection against mechanical risks and for protection of welders.

### LEVELS OF PROTECTION:



#### MECHANICAL RISKS

|                       |   |
|-----------------------|---|
| abrasion resistance:  | 3 |
| cut resistance:       | 1 |
| tear resistance:      | 3 |
| puncture resistance:  | 3 |
| cut resistance (TDM): | x |



#### THERMAL RISKS

|                               |   |
|-------------------------------|---|
| fire resistance:              | 4 |
| contact heat resistance:      | 1 |
| convection heat resistance:   | 3 |
| heat of radiation resistance: | x |
| small spatter resistance:     | 4 |
| big spatter resistance:       | x |

This personal protective equipment is in conformity with these harmonized European Standards:

ČSN EN 420:2004+A1 2010 : Protective gloves - General requirements and test methods.  
 ČSN EN 388:2016 : Protective gloves against mechanical risks. (3-1-3-3-x)  
 ČSN EN 407:2005 : Protective gloves against thermal risks. (4-1-3-x-4-x)  
 ČSN EN 12477:2002/A1:2005 : Protective gloves for welders. Class 1.

Certified by notified body č. 1023 (ITC a.s. Zlín),  
 Certificate 18 0376 T/NB.

Pairs in carton: 120  
 Carton weight: 20 kg  
 Carton size: 0,087 m<sup>3</sup>  
 Polybag packing (pairs): 12

Store in dry and dark environment. Clean dirt with brush. Gloves can not be washed or cleaned chemically. Do not expose gloves to heat of radiation, organic solvents and their fumes, lubricants, grease, mineral oils, caustics and water.

Warning: Gloves can not be used in environment where there is risk of glove being caught by moving parts of machine.