



# TECHINCAL SHEET

FA 20 300 02

**Designation** : Webbing Retractable Fall Arrester

- Webbing width : 50 mm
- Minimum breaking strength : > 15 kN
- Fall indicator on the top of the device
- Protective casing
- Energy Absorber width 45 mm

**Connector** :

1 screw-locking karabiner opening 17 mm, réf. FA5010117 for connection on a harness.

**Compliance** – Conforms to EN 360:2002



**Length** : 2.50 m

**Material of the components** :

Casing : Polyethylene anti shock  
Webbing : Polyamide / Polyester  
Connector : Steel

**HS code**

84289090

**Carton Size / Pieces**

71x33x21 / 20

**Unit weight**

1.23 kg

**AET : N° 2194 Issue 3 Extension 1**

Satra Technology Centre, N°0321  
Wyndham Way, Telford Way, Kettering,  
Northamptonshire, NN16 8SD, United Kingdom.

**Article 11 : GB07/73551**

SGS United Kingdom Ltd., N° 0120  
Unit 202B, Worle Parkway,  
Weston-super-Mare, BS22 6WA, United Kingdom



maj : 04/12

ZI les portes du Dauphiné  
4 rue de l'Aigüe  
69 780 St Pierre de Chandieu – France  
Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32  
www.kratossafety.com info@kratossafety.com

