



TECHNICAL DATA SHEET

FLYTEX S1P SRC ESD

Safety shoes

Article NO: G3354

Upper: knitted two-layer textile - type 3D KNIT

Liner: laminated breathable textile MESH

Sole: PU/PU

Size: 35 - 50



Safety shoe with a sporty design, upper made with seamless "3D KNIT" technology. The braided upper consists of two layers of textile in a contrasting color design. Reinforcement by offset printing in the area of the toe and around the laces. The breathability of the shoes is ensured by the laminated MESH fabric in the area of the lining and the tongue. ANATOMIC GEL insole with a cushioning gel element in the heel part. The stable polyurethane sole made by direct spraying provides the highest level of anti-slip properties. The shoes are equipped with a composite toe and a kevlar insole against punctures. The model protects against electrostatic discharge.

Type and degree of protection:

Category	EN ISO 20345
Antistatic properties	X
Absorption of energy in the heel area	X
Sole with pattern- oil resistance	X
Puncture resistance (kevlar insole)	X
Composite toecap for toe protection	X
Slip resistant ceramic tile floor with SLS and on steel floor with glycerol (SRC)	X



This personal protective equipment is in conformity with this harmonized European Standard:

EN 20345:2011 - Personal protective equipment - safety shoes.



Slip resistance on ceramic tile floor with SLS and on steel floor with glycerol (SRC mark).

Certified by notified body no. 2369 ((VIPO a.s., Gen. Svobodu 1069/4, 958 01 Partizánske, Slovakia), certificate number 00109/111/1/2020.

Pairs in carton: 10
Carton weight (for size 43): 13,2 kg
Carton size: 0,086 m³

The shoes have to be perfect as for from and size, because they have rigid parts. The right size has to be found by measuring practically and carefully the shoes. The closing system has to be used correctly. The laces have to be tightened well without leaving too long free tops. The shoes have to be cleaned and treated with right, specific products, following the instructions for use. Do not keep footwear near heatings when not used and let them dry in a windy or room temperature. Before wearing and when cleaned, the shoes have to be controlled in order to find out visible defects existing, like closing system function, outsole profile's water, possible damages, etc. To define the right type of footwear to wear in every environment, the possible dangers and the place/ environment have to be included (e.g. construction industry, high temperatures, etc.). The shoes have to be stored correctly, keeping them in the proper packing.
