



TECHNICAL SHEET

FA 20 100 10

Designation : Anchor line for fall arrester FA 20 100 00A or B

- Made up of 14-16 mm diametre polyamide twisted rope
- Abrasion resistant thimble to protect the loops from being damaged by metallic contact
- Spliced end protected with a strong transparent covering sleeve.
- Colored tracer strand which loses colour to show that the lanyard is unfit for use.

Compliance : Conforms to EN 353-2 : 2002

Length : 10 mtrs

Also exists in 20, 30, 40, 50, 100, 200 mtrs
Other length on request.

Material of the components :

Rope : Polyamide



HS code

56090090

Carton Size / Pieces

80x40x24 / 10

Unit weight

1,25 kg

AET : N° 2664 Issue 3 Extension 3

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



MAJ : 02/15

ZI les portes du Dauphiné

4 rue de l'Aigue

69 780 St Pierre de Chandieu – France

Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32

www.kratossafety.com info@kratossafety.com

