

TECHNICAL DATA SHEET

4TIG

Leather and welding gloves

Article NO: A2013
 Material: sheep skin
 Cuff: soft cowsplit
 Size: 8"/M - 11"/XXL



Gloves are meant for protection against mechanical risks and also as protection for welders. Length 35 cm, protected seams, cotton lining.

LEVELS OF PROTECTION:

EN 388



MECHANICAL RISKS

| | |
|-----------------------|---|
| abrasion resistance: | 2 |
| cut resistance: | 1 |
| tear resistance: | 2 |
| puncture resistance: | 2 |
| cut resistance (TDM): | X |

EN 407



THERMAL RISKS

| | |
|-------------------------------|---|
| fire resistance: | 4 |
| contact heat resistance: | 1 |
| convection heat resistance: | 2 |
| heat of radiation resistance: | X |
| small spatter resistance: | 4 |
| big spatter resistance: | X |

This personal protective equipment is in conformity with these harmonized European Standards:

HRN EN 388:2016 (EN 388:2016): Protective gloves against mechanical risks.

HRN EN 407:2005 (EN 407:2004): Protective gloves against thermal risks.

HRN EN 420:2011 (EN 420:2003+A1:2009): Protective gloves - General requirements and test methods.

HRN EN 12477:2001+A1:2005 (EN 12477:2001+A1:2005): Protective gloves for welders. - Class B.

Certified by notified body no. 2474 (MIRTA-KONTROL d.o.o., Gradiška 3, HR-10040 Zagreb-Dubrava, Croatia),
 Certificate number OZO311-CPT00619.

| | |
|--------------------------|----------------------|
| Pairs in carton: | 120 |
| Carton weight: | 14 kg |
| Carton size: | 0,068 m ³ |
| Polybag packing (pairs): | each pair |
| Master polybag: | 12 pairs |



Store in dry and dark environment. Clean dirt with brush. Gloves can not be washed or cleaned chemically. Do not expose gloves to heat of radiation, organic solvents and their fumes, lubricants, grease, mineral oils, caustics and water.

Warning: Gloves can not be used in environment where there is risk of glove being caught by moving parts of machine.
