

TECHNICAL DATA SHEET

M5200

Eye protection

Article NO: E4046

Lens: vellow

Material- lens: polycarbonate Material- frame: polycarbonate



Extremely light safety glasses with rimless design which weights only 22 g. Panoramic visor made from a single piece fits perfectly to every type of face. Nose bridge is integrated and in the end of temples are holes for possibility of connection of cord. Yellow lens are antifogging, anti-scratching and resistant to low-energy shocks (up to 45 m/s) at extreme temperatures ($-5 ^{\circ}\text{C} - +55 ^{\circ}\text{C}$).



Adjustable temple length - NO



Adjustable temple angle - NO



Anti-fogging lens - YES



Anti-scratching lens - YES

Clear lens, UV, 2-1.2 1 FT O

Type of filter: 2 UV filter Shade number: 1.2 yellow

Optical class: 1 permanent use

Mechanical resistance: FT resistant to low-energy shocks at extreme

temperatures

Type of the lens: O original lens

This personal protective equipment is in conformity with these harmonized European Standards:

EN 166:2001: Personal eye protection. General requirements.



Certified by notified body no. 2797 (BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands), Certificate number 692741, dated 17th July 2020.

Pieces in carton: 250
Pieces in box: 10
Polybag packing (pieces): 1
Carton weight: 12 kg
Carton size: 0,103 m³

Store in dry and dark environment away from direct sunlight at temperatures of -5°C to +55°C, relative humidity 90% and out of sources of gasoline vapors and solvents.

It is recommended to clean after each use. Clean at room temperature with a clean cloth, lightly moistened with a concentrated solution of water and detergent. Do not use hot water, fuel, degreasing fluids, organic solvents or abrasive cleaners.