

## TECHNICAL DATA SHEET

HOUSTON

Sewn layered gloves

Article NO: A4001

Material: sewn cotton interlock dipped in nitrile

elastic

Wrist:

Size: 7"/ S - 10"/ XL



Gloves are meant for protection against mechanical risks.

## LEVELS OF PROTECTION:



## 388 MECHANICAL RISKS

abrasion resistance:	2
cut resistance:	Х
tear resistance:	1
puncture resistance:	1
cut resistance in according with ISO:	Х

This personal protective equipment is in conformity with these harmonized European Standards:

EN 420:2003+A1:2009: Protective gloves- general requirements EN 388:2016 : Protective gloves against mechanical risks (3-1-2-1-X)

Certified by notified body no. 2369 (VIPO a.s., Slovakia), Certificate number 00249/111/1/2019.

Pairs in carton:	240
Carton weight:	13 kg
Carton size:	0,066 m <sup>3</sup>
Polybag packing (pairs):	12

Store in dry and dark enviroment. Clean dirt with brush. Gloves can not be washed or cleaned chemically. Do not expose gloves to heat of radiation, organic solvents and their fumes, lubricants, grease, mineral oils, caustics and wat.

Warning: Gloves can not be used in enviroment where there is risk of glove being catched by moving parts of machine.