



TECHNICAL SHEET

FA 40 903 20

Designation:

Work positioning kernmantle lanyard with grip adjuster

- Made up of 12mm diam polyamide kernmantle rope
- Abrasion resistant thimble to protect the loops from being damaged by metallic contact
- Sewings protected under a strong protective sleeve which allow a visual checking of the sewings
- Grip adjuster for a progressive movement

Connectors:

1 steel screw-locking karabiner opening 17 mm, réf. FA5010117, and 1 snap hook FA 50 202 17.

Compliance: EN358: 2000



Length :

Maximum length : 2 mtr

Material:

Lanyard: polyamide
Connectors and grip adjuster: steel

HS code

56075090

Carton size / Pieces

71x33x21 / 25

Unit weight

0.99 Kg

AET: N° 3884 Issue 1 Extension 3

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



Maj.: 04/14

ZI les portes du Dauphiné
4 rue de l'Aigue
69 780 St Pierre de Chandieu – France
Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32
www.kratossafety.com info@kratossafety.com

